Overview

10.4.2 Configure CRC Application Directory Properties · https://i2b2.org/docs/10-4-2-configure-crc-application-directory-properties/

Step 3: Configure the Application Directory properties

The **third step** in the cell configuration process is to edit the **crc_application_directory.properties** file for edu.harvard.i2b2.crc. During this step you need to specify a location for the application properties directory. This location can be anything you desire but it must be a directory path that the Windows or Linux user has been granted permission to access.

Steps to update crc_application_directory.properties

1. At the command prompt type the following:

Linux Command
open *YOUR_I2B2_SRC_DIR*/edu.harvard.i2b2.crc/etc/spring/crc_application_directory.properties

Windows Command
YOUR_I2B2_SRC_DIR\edu.harvard.i2b2.crc\etc\spring\crc_application_directory.pro ry.properties

EXAMPLES:

Linux Command: open /opt/i2b2/edu.harvard.i2b2.crc/etc/spring/crc_application_directory.properties

Windows Command: C:\opt\i2b2\edu.harvard.i2b2.crc\etc\spring\crc_application_directory.pro ry.properties

2. The **crc_application_directory.properties** file will open. Set the following properties to reflect your environment:

Application properties for CRC Cell
edu.harvard.i2b2.crc.applicationdir=/*YOUR_JBOSS_HOME_DIR*/standalone/configuration/crcapp

3. Save the changes and close the file.