Overview

10.4.5 Data Source Configuration · https://i2b2.org/docs/10-4-5-data-source-configuration/

Step 12: Configure the data sources

The CRC cell needs to communicate with your **i2b2 database** and in order to do this it needs to know where the tables for the **demodata** and **hivedata** reside. Therefore the **twelfth** and **final step** in the cell configuration process is to configure the data sources for the CRC Cell. This information is configured in the **crc-ds.xml** file.

Things to keep in mind when configuring your datasources:

- The **demodata** and **hivedata** tables were created during the chapter on Data Installation.

- The **CRCBootStrapDS** points to the data source for your CRC_DB_LOOKUP table which is a hivedata table.
  - The and need to match the database user you set up for your hivedata. In the i2b2 demo database this is *i2b2hive* and *demouser*.

- The **QueryToolDemoDS** points to the data source for your demodata tables.
  - The and need to match the database user you set up for your demodata. In the i2b2 demo database this is *i2b2demodata* and *demouser*.

- The needs to have the following:
  - The correct JDBC information for your type of database.
  - The correct location of the database containing your crcdata or hivedata tables. *(These may or may not reside in the same location)*

- Both the and need to accurately reflect the type of database you are connecting to.

Steps to configure data sources

The following steps define how to configure your data sources for the CRC Cell. These steps include example configurations for Oracle, PostreSQL and SQL Server.

1. The **crc-ds.xml** file is located in the following directory:

YOUR_I2B2_SRC_DIR\edu.harvard.i2b2.crc\etc\jboss

2. Open the crc-ds.xml file to configure your data sources. *(see examples shown below)*

Oracle Database

PostgreSQL Database

SQL Server Database

3. If your environment has multiple projects pointing to different data sources then copy the section for each project data source.

4. Update the **jndi-name** and **pool-name** to reflect the name of the second project .

Example: A second project called Demo2 would have the following entry:

Second Data Source Configuration

Note

The above example is for an Oracle database. If your database is SQL Server or PostgreSQL then you will need to copy the section for your type database connection. Do not use this one as it will not work.

5. Save the changes and close the file.