Overview

11.4 Configuration · https://i2b2.org/docs/11-4-configuration/

Configure the Workplace Cell for Installation

As stated in the previous section, there are a number of files in the **edu.harvard.i2b2.workplace** directory that will need to be edited to reflect the appropriate configuration at your site. The following outlines the steps that need to be taken during the configuration stage of the installation.

Step 1: Change your working directory

Step 2: Configure the build properties

Step 3: Configure the Workplace Application Directory properties

Step 4: Workplace properties: Set location of Hivedata tables

Step 5: Workplace properties: Configure PM Cell Properties

Step 6: Configure the data sources

Note

The configuration files you will be editing are delivered with examples. In some instances these files may contain multiple examples for the three different database management systems supported by the i2b2.

Assumptions

The steps in this section are based on the following assumptions

Linux: your user has the appropriate ***administrative access*** to the opt directory.

Windows: You are logged into the Windows Command Prompt as an ***Administrator***.

If you do not have the appropriate access you will have problems running the scripts.

Step 1: Change working directory

The **first step** in the cell configuration process is to change your working directory to the location of your **edu.harvard.i2b2.workplace folder**.

Change Directory Command
CD *YOUR_I2B2_SRC_DIR*\edu.harvard.i2b2.workplace

Important

The change directory command shown above is written for Windows. The command itself is the same for both Linux and Windows with the only exceptions being the slashes in the path name and Linux does not include the "drive".

- *Linux Path:* use a forward slash.
- *Windows Path:* use a backward slash.

EXAMPLES:

Linux Command: CD /opt/i2b2/edu.harvard.i2b2.workplace

Windows Command: CD C:\opt\i2b2\edu.harvard.i2b2.workplace